

DIGITEX



Simplicity and functionality
Advanced security
Flexible installation

Tecnoalarm
Hi-Tech Security Systems

The DIGITEX keypad replaces the TP SDN
maintaining the same compatibility
with the Tecnoalarm systems.

TP4-20

TP4-20 GSM

TP8-28

TP8-28 GSM

TP8-64

TP8-64 BUS

TP8-88

TP8-96 VIDEO

TP16-256

TP16-512



DIGITEX





- **Keypad for outdoor mounting**
- **Surface mounting**
- **Touch-sensitive steal membrane**
- **Grazing keypad lighting with LED light strip**
- **User interface: 7 signaling LED and buzzer**

DIGITEX > Advantages

TIGHTNESS

IP65 waterproof casing with
6m prewired connection cable

SOLIDITY

Vandal-proof aluminum
die-cast casing

ELEGANCE

Simple and elegant design



Technical and functional specifications



GENERAL FEATURES	Description	Keypad for outdoor mounting
	Connection	Bus RS485
	Manageable programs	4
SIGNALING	Optical	7 signaling LED
	Acoustic	Buzzer
ELECTRICAL SPECIFICATIONS	Rated voltage	12V DC
	Operating voltage	10V...15V DC
	Min. consumption	10mA @ 12V DC
	Max. consumption (LED + keypad lighting on)	136mA @ 12V DC
ANTI-TAMPER PROTECTION	Anti-opening and anti-detachment	Magnetic - reed switch
	Anti-magnet	Magnetic - reed switch
CLIMATIC SPECIFICATIONS	Environmental class	IV
	Operating temperature	-25°C...+60°C (under test)
	Relative humidity	10%...93% (without condensation)
PHYSICAL SPECIFICATIONS	Connection cable	6m prewired
	Protection class	IP65
	Casing	die-cast aluminum
	Dimensions (L x H x D)	81 x 121 x 24mm
	Weight	510g

Tecnoalarm

Via Ciriè, 38 - 10099 San Mauro Tse - Torino (Italy)
tel. +390112235410 - fax +390112735590
tecnoalarm@tecnoalarm.com
www.tecnoalarm.com

Tecnoalarm FRANCE

495, Rue Antoine Pinay - 69740 Genas - Lyon (France)
tél. +33478406525 - fax +33478406746
tecnoalarm.france@tecnoalarm.com
www.tecnoalarm.com
Agence de Paris: 125, Rue Louis Roche - 92230 Gennevilliers

Tecnoalarm ESPAÑA

c/Vapor 18 (Pol. Ind. El Regas)
08850 Gavà - Barcelona (España)
tel. +34936622417
tecnoalarm@tecnoalarm.es
www.tecnoalarm.com

